



The 3200NXT Network Controller uses on-board communication capabilities to link multiple commercial valves (via off-the-shelf CAT3, CAT5, or better cables) for a variety of system types. The 3200NXT is configured for use with Fleck® 2750, 2850s, 2900s, 3150, and 3900 Control Valves, and also supports stager valves using butterfly or notched cams.

### Features

- 2x16 character backlit LCD display
- Networks up to four valves
- Field-configurable for System Types 4, 5, 6, 7, and 9
- Auxiliary inputs and outputs
  - Remote signal start input
  - Remote lockout input
  - Programmable relay output/chemical pump output
- Easy installation with plug-in wiring harnesses
- Front panel diagnostics button
  - Flow rate
  - Peak flow rate
  - Totalizer
  - Hours between last two regenerations
  - Hours since last regeneration
  - Adjustable volume remaining
  - Valve position
  - Software version
- Easy time of day adjustment
  - Simply push the up or down button on the lead (#1) controller; time of day is automatically copied to the remaining controllers
- Five configurable cycle steps
- Remote signal start can be used simultaneously with time clock, meter immediate, or meter delayed regeneration triggers
  - Allows monitoring of flow and volume information in RSS applications

### Three programming levels

- User mode
- Master programming
- Diagnostics mode